



POWER SYNTHETIC OIL 15W-40

It is a high-performance synthetic technology lubricant for diesel engines that helps extend engine life in severe on- and off-highway applications. (Recommended for Ecuador 15,000 km.) The advanced chemistry of these products provides exceptional performance in modern engines, even those with Exhaust Gas Recirculation (EGR) systems, as well as in older engines that run with low or high sulfur fuels.

POWER SYNTHETIC OIL 15W-40 is recommended for use in a wide range of heavy-duty applications and in the operational environments found in the transportation industries, both in trucks operating at high speeds and long distances, and in urban service buses, with Frequent starts and stops. These products will provide exceptional protection on most demanding diesel engines from Caterpillar, Cummins, Detroit Diesel, Mack, Mercedes Benz, Navistar, Volvo, and others. It also meets the API SM specification for gasoline engines and mixed fleets.

Quality Standards: Meets or exceeds: - API CJ-4, CI-4, CH-4, CG4, CF-4 / SM.

- ACEA E9, A3/B3
- DHD-1 - MB
228.3 - Navistar
International - MAN M3477

- Volvo VDS-4 - Mack
EO-O PP - Cummins CES
20081 - DD 93K218 - Caterpillar
ECF-3 - DEUTZ III-05
- VW 505 - SCANIA LDF-2 -
ISUZU DEO - Renault
RLD-2

Trucks

Health and security:

This product does not present a health or safety hazard when used properly in the recommended application.

Avoid contact with skin. Review the health and safety sheet for more information.

Storage:

If possible, store indoors. The product should not be stored at temperatures above 60°C, higher than exposed to the sun or freezing.

PARAMETER	METODO ASTM	SAE 15W-40 CJ-4
Cinematıcal viscosity @40 �C	D 445	112.55
Cinematıcal viscosity @100 �C	D 445	15
Viscosity Index	D 2270	139
Density @ 150C Kg/l	D 4052	0.8469
Pour Point, �C	D 97	-27
Flash Point, �C	D 92	230
TBN, mg / KOH / g	D 2896	10
Sulfated ashes, % weight	D 874	1.1



516S 25th W Ave, Tulsa, Ok 74127 USA