



PREMIUM SYNTHETIC OIL

It is an oil for conventional engines formulated with type II lubricant bases reinforced with synthetic technology and with the most advanced additive chemistry. (Recommended for Ecuador 15,000 km.) This lubricant contains active cleaning agents, which not only help prevent dirt and contaminants from entering the engine, but also improve its performance by eliminating deposits and sediments. It is specially formulated to provide additional protection against the harmful effects of urban driving with frequent stops and starts, and with high and low vehicle operating temperatures.

motor.

It is formulated to give you the highest confidence in protection that goes beyond conventional oils. They are particularly recommended for the following types of vehicles and conditions: Latest technology and high performance gasoline engines, Passenger vehicles, SUVs, light trucks and vans driven in the city with many stops, Operational conditions.

PARAMETER	METHOD ASTM	SAE 5W-30	SAE 10W-30	SAE 10W-40	SAE 15W-50	SAE 20W-50
Kinematic viscosity @ 40 °C	D 445	61.4	66.3	96	128	154.3
Kinematic viscosity @ 100 °C	D 445	10.4	10.4	14.5	18	19
Viscosity Index	D 2270	159	145	157	157	141
Density @ 150C Kg/l	D 4052	0.847	0.867	0.870	0.870	0.880
Pour Point, °C	D 97	-33	-33	-30	-39	-30
Flash Point, °C D 92		224	220	230	232	230
Sulphated ash, % weight	D 874	0.83	0.82	0.92	0.84	0.85
HTHS viscosity, mPa*s @ 150°C	D4683	3.11	3.14	4.0	4.5	4.66

PERFORMANCE AND BENEFITS

- Advanced engine cleaning, removing sediment deposits on engine surfaces and dissolving them safely in the oil.
- Advanced protection against wear.
- Advanced control against oxidation and deposits, products of combustion.
- Helps protect emissions systems.
- Long change times, thanks to the synthetic technology with which they are formulated.
- Notable fuel savings especially for viscosity grades that comply with ILSAC GF-5.

Quality Standards: Meets or exceeds: -

API SN, SM, SL - ACEA A3/B4 - Ford
M2C 913C - GM 6094M-MB 229.3

- VW 502.00

In addition, for the SAE grade 5W30 and 10W30 it
complies with: - ILSAC GF-5 - VW 502.00/505.00 -

BMW LL-01

- MB 229.3/229.5 For the SAE

10W40 viscosity grade, it also complies with: - API

CF - VW 502.00/505.00 - BMW LL-01 - MB
229.3/229.5

Health and security:

This product does not present a health or safety
hazard when used properly in the recommended
application.

Avoid contact with skin. Review the health and
safety sheet for more information.

Storage:

If possible, store indoors. The product should not be
stored at temperatures above 60°C, higher than
exposed to the sun or freezing.